

FIBREGLASS DOUBLE-SIDED LADDER



Standard
UNE-EN 131

Standard
UNE-EN 50528

Insulation
100 KV

Ref.	Nº Rungs			Kg
FT05	5	1490	580	9
FT06	6	1770	590	10
FT07	7	2050	620	12
FT08	8	2330	650	13
FT09	9	2660	680	15
FT10	10	2940	710	16
FT11	11	3220	740	18
FT12	12	3500	770	19
FT13	13	3780	800	25
FT14	14	4060	830	26
FT15	15	4340	860	28
FT16	16	4620	890	29



Ref. FT07



Anti-splay restraint strap



Stabiliser

FIBREGLASS DOUBLE-SIDED LADDER WITH A THIRD FLY SECTION

The fly section can be separated.



Standard
UNE-EN 131

Standard
UNE-EN 50528

Insulation
100 KV

Ref.	Profiles dimensions	Nº sections x nº rungs				Kg
FTE05	60x20	3x5	1490	2395	650	14
FTE06	60x20	3x6	1770	2955	680	16
FTE07	60x20	3x7	2050	3515	710	18
FTE08	60x20	3x8	2330	3795	740	20
FTE09	60x20	3x9	2660	4400	770	22
FTE10	60x20	3x10	2940	4960	800	24
FTE11	70x26	3x11	3220	5240	830	33
FTE12	70x26	3x12	3500	5800	860	36



Ref. FTE09



Locking system



Double-sided ladder



Fly section as a single section ladder